

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




135033203
FM CASE 3032

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16D 55/36		A1	(11) International Publication Number: WO 00/09900
			(43) International Publication Date: 24 February 2000 (24.02.00)
(21) International Application Number: PCT/GB99/02477 (22) International Filing Date: 28 July 1999 (28.07.99) (30) Priority Data: 9817747.0 15 August 1998 (15.08.98) GB (71) Applicant (for all designated States except US): FEDERAL-MOGUL TECHNOLOGY LIMITED [GB/GB]; Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): BUNKER, Kenneth, James [GB/GB]; 39A Mill Road, Rearsby, Leicester LE7 4YN (GB). (74) Agent: DRURY, Peter, Lawrence; T & N Limited, Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: DISC BRAKE



(57) Abstract

A disc brake (10) comprises a disc (12, 14), friction material pads (26) arranged on opposite sides of the disc, and an operating mechanism (50, 52) operable to bring the pads into contact with the disc so that the pads apply a braking force to the disc. The brake (10) also comprises a slideway (72a) on which at least one of said pads (26) is supported for sliding movement towards or away from the disc (12, 14). Said slideway (72a) is formed by a guidance member (72) which defines at least two parallel grooves (72b) in a surface (72c) of the guidance member. The grooves (72b) extend parallel to the direction of the slideway (72a). The guidance member (72) is supported by parallel rods (70) which are received in said grooves (72b).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DISC BRAKE

This invention is concerned with a disc brake, eg for the wheel of a vehicle.

In WO 98/25804, there is disclosed a disc brake which comprises two discs mounted on the same hub to rotate with the hub about a central axis of the hub, and friction material pads arranged on opposite sides of both discs including two pads between the discs. The discs are slidable axially on the hub and the pads are slidable in a parallel direction except for one pad which is fixed relative to the hub. Said disc brake also comprises an operating mechanism operable to bring the pads into contact with the discs to apply a braking force thereto. The brake also comprises a slideway on which at least one of said pads is supported for sliding movement towards or away from the disc. The slideway comprises a guidance member on which the movable pads are slidably-supported, ie the guidance member provides a slideway on which pads are supported for movement towards or away from said discs. The operating mechanism, which comprises a hydraulically-operated piston and cylinder assembly, the cylinder of which is fixed on a suspension link. The operating mechanism operates to move a first of the pads on the slideway into contact with a first of the discs, causing movement of the first disc on the hub to bring the other pad associated with that disc into contact with the first disc. The movement continues moving the pads which are between the discs so that one of them contacts the second disc which moves into contact with the other pad associated with the second disc which is the pad which is fixed relative to the hub. The guidance member is supported by

bolts which pass therethrough and fix it to said cylinder. As further explained in WO 98/26191, the bolts enable the bending and shearing forces applied to the pads during operation of the brake to be taken by the bolts while the guidance member itself can be made from lower strength material. The slideway is relatively complex to assemble and requires relatively long holes to be drilled through the guidance member to receive said bolts.

It is an object of the present invention to provide a disc brake having a simplified slideway which is easier to assemble.

The invention provides a disc brake comprising a disc, friction material pads arranged on opposite sides of the disc, and an operating mechanism operable to bring the pads into contact with the disc so that the pads apply a braking force to the disc, the brake also comprising a slideway on which at least one of said pads is supported for sliding movement towards or away from the disc, characterised in that said slideway is formed by a guidance member which defines at least two parallel grooves in a surface of the guidance member, the grooves extending parallel to the direction of the slideway, the guidance member being supported by parallel rods which are received in said grooves.

In a disc brake according to the invention, the grooves in the guidance member are much easier to form than long holes through the guidance member and, in assembling the brake, the guidance member can simply be fitted over the rods.

A disc brake according to the invention may be of the type disclosed in WO 98/25804. That brake comprises two discs which are slidable on the same hub under the control of leaf springs which act between the hub and the discs.

The brake also comprises a cylinder which is integrally formed with a suspension link and a caliper also fixed to the suspension link, the caliper having supports for friction material pads mounted thereon.

Preferably, in a disc brake according to the invention said guidance member defines a protuberance between said grooves, the protuberance being a close fit between two of the rods.

The rods are, preferably, provided by bolts.

The guidance member may be made of plastics material or metal such as aluminium. Preferably, the guidance member is formed as an extrusion, since the guidance member can be formed with a constant transverse cross-sectional shape.

There now follows a detailed description, to be read with reference to the accompanying drawings, of a disc brake which is illustrative of the invention.

In the drawings:

Figure 1 is a vertical cross-sectional view taken through the illustrative disc brake; and

Figure 2 is a perspective view on an increased scale of a guidance member of a caliper of the illustrative disc brake.

The illustrative disc brake 10 shown in Figure 1 is for a wheel (not shown) of a car. The brake 10 comprises a disc 12, a further disc 14, and a hub 16, on which the wheel can be mounted. The discs 12 and 14 and the hub 16 are arranged to rotate about a common central axis 18.

The hub 16 comprises an internally splined hollow inner cylindrical portion 16a which is arranged to receive

a drive shaft (not shown) which drives the wheel. The hub 16 also comprises an external flange 16b at one end of the portion 16a. This flange 16b has bolt holes (not shown) through which the wheel can be bolted to the flange 16b in a conventional manner. The flange 16b also serves to connect the portion 16a to an outer hollow cylindrical portion 16d of the hub 16.

The two discs 12 and 14 are mounted on the cylindrical outer surface of the hub portion 16d so that the hub 16 and the two discs 12 and 14 rotate as a unit about the axis 18 and the discs 12 and 14 can perform axial sliding movement on said hub 16. Specifically, four grooves 20 are formed in the outer cylindrical surface of the portion 16d of the hub 16 and four teeth 22 which project inwardly from each of the discs 12 and 14. The teeth 22 enter the grooves 20 and are a sliding fit therein.

The brake 10 also comprises four friction material pads 26 which are arranged with two of the pads 26 on opposite sides of each of the discs 12 and 14. The pads 26 are for braking the discs 12 and 14 by engaging side surfaces of the discs. The friction pads 26 are secured to three backing plates 28, one backing plate 28a being between the discs 12 and 14 and the others being on opposite sides of the discs 12 and 14 to the plate 28a. The median plate 28a has friction material pads 26 secured to both of its faces. When the brake is applied, a movable outer friction material pad 26 is moved until the four pads 26 and the discs 12 and 14 are all in contact with one another, the discs 12 and 14 and the plate 28a sliding axially to accommodate this movement.

The brake 10 also comprises resilient means in the form of four leaf springs 32 mounted on the hub 16 and engaging the discs 12 and 14 so that the springs 32 apply force radially between each of the discs 12 and 14 and the

hub 16. The leaf springs 32 are equally distributed circumferentially around the hub 16, each being mounted on one of the bottom surfaces of the grooves 20, ie each spring 32 is mounted in one of the grooves 20 and acts between the bottom surface of the groove and an inner surface of the teeth 22 which enter the groove 20.

The illustrative brake 10 also comprises an operating mechanism operable to bring the pads 26 into contact with the discs 12 and 14. The operating mechanism is in the form of a piston and cylinder assembly comprising a piston 50 and a cylinder 52, the cylinder 52 is fixed relative to the axis 18 being integral with a suspension link (not shown) of the vehicle as disclosed in WO 98/25804. The assembly 50, 52 is operable to move a first of the pads 26 into contact with the disc 12 and to cause relative movement between the assembly 50, 52 and the disc 12 to bring the other pad 26 associated with the disc 12 into contact with the disc 12, so that the pads 26 apply a braking force to the disc 12. Specifically, a caliper 54 is mounted on the cylinder 52 and bridges the edges of both discs 12 and 14. The furthest pad 26 from the cylinder 52 has its support plate 28 fixedly mounted on the caliper 54 while the support plates 28 of the remaining pads 26 are slidable on the caliper 54. When the piston 50 is moved outwardly from the cylinder 52 by hydraulic fluid under pressure, it directly presses the support plate 28 of the nearest pad 26 so that the plate 28 slides on the caliper 54. The nearest pad 26 presses the disc 12 so that it slides on the hub 16. The disc 12, in turn, presses on the pad 28 on the opposite side thereof causing the support plate 28a to slide on the caliper 54. The movement of the plate 28a causes the pad 26 on the plate 28a which faces the disc 14 to contact the disc 14. The disc 14 slides on the hub 16 until it contacts the pad 26 on the plate 28 which is fixed to the caliper 54. The brake 10 is now "on"

with the discs 12 and 14 both engaged on both sides by one of the pads 26.

The caliper 54 comprises two rods 70 (Figure 2) which extend parallel to one another axially of the hub 16. The rods 70 are provided by bolts which pass through holes (not shown) in the plate 28 which supports the pad 26 which is furthest from the cylinder 54. The bolts are also received in tapped holes (not shown) in the cylinder 52. Bolts of this type are disclosed in WO 98/26191. The bolts may also be arranged to extend in the opposite direction, ie the bolts pass through holes in the cylinder 52 and are received in tapped holes in the furthest plate 28. The caliper 54 also comprises a guidance member 72 which forms a slideway of the brake 10 on which the movable pads 26 are supported for sliding movement towards or away from the discs 12 and 14. Specifically, the guidance member 72 comprises oppositely-facing arcuate side surfaces 72a on which hook-like projections of the support plates 28 of the movable pads 26 are slidable.

The guidance member 72 also defines two parallel grooves 72b in a lower surface 72c thereof. The grooves 72b extend parallel to the direction of the slideway defined by the surfaces 72a and are arranged to be a close fit over the rods 70. The guidance member 72 is supported by the rods 70 which are received in said grooves 72b and is held in position between the fixed plate 28 and the cylinder 52 by clamping force applied by the bolts 70 which form the rods.

The guidance member 72 also comprises a protuberance 72d between said grooves 72b, the protuberance 72d being a close fit between said rods 70.

The guidance member 72 has a constant transverse cross-sectional shape and is formed of aluminium as an

extrusion, although other materials, including plastics materials such as glass fibre re-inforced phenolic resin, could be used.

The guidance member 72 is easily assembled on the rods 70 by fitting the grooves 72b over the rods 70.

CLAIMS

- 1 A disc brake (10) comprising a disc (12, 14), friction material pads (26) arranged on opposite sides of the disc, and an operating mechanism (50, 52) operable to bring the pads into contact with the disc so that the pads apply a braking force to the disc, the brake also comprising a slideway (72a) on which at least one of said pads (26) is supported for sliding movement towards or away from the disc (12, 14), characterised in that said slideway (72a) is formed by a guidance member (72) which defines at least two parallel grooves (72b) in a surface of the guidance member, the grooves extending parallel to the direction of the slideway, the guidance member being supported by parallel rods (70) which are received in said grooves.
- 2 A disc brake according to Claim 1, characterised in that said guidance member (72) defines a protuberance (72d) between said grooves (72b), the protuberance being a close fit between two of the rods (70).
- 3 A disc brake according to either one of Claims 1 and 2, characterised in that said rods (70) are provided by bolts.
- 4 A disc brake according to any one of Claims 1 to 3, characterised in that the guidance member (72) is made of plastics material.
- 5 A disc brake according to any one of Claims 1 to 4, characterised in that the guidance member (72) is formed as an extrusion.





Fig. 1

2/2

*Fig. 2*

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/02477

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16D55/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 1 530 461 A (GEN MOTORS FRANCE) 1 November 1978 (1978-11-01) page 2, line 32 - line 52; figures 1-3	1
A	EP 0 054 779 A (EATON CORP) 30 June 1982 (1982-06-30) abstract	1
A	DE 30 42 601 A (TEVES GMBH ALFRED) 24 June 1982 (1982-06-24) figures 1-3	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

1 October 1999

Date of mailing of the international search report

18/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Overbeeke, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/02477

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 1530461 A	01-11-1978	DE 2605805 A FR 2302453 A	02-09-1976 24-09-1976
EP 0054779 A	30-06-1982	AU 545806 B AU 7870781 A BR 8108127 A CA 1168995 A ES 508256 A US 4749066 A	01-08-1985 01-07-1982 28-09-1982 12-06-1984 01-11-1982 07-06-1988
DE 3042601 A	24-06-1982	NONE	